



I-ROD® ADHESIVE HIGH-STRENGTH ADHESIVE FOR SECURING I-ROD® STRIPS

I-Rod Adhesive provides a strong, permanent bond between I-Rod strips and pipe supports.

I-Rod adhesive is designed to securely anchor strips of I-Rod in situations where drilling and bolting would be difficult. It's a great solution for using I-Rod on solid concrete supports that can't be fitted with U-Bolts, or for locations where drilling through metal is restricted or would require a hot work permit.

A strong bond

I-Rod Adhesive provides an extremely strong bond between I-Rod's tough thermoplastic material and the steel or concrete surfaces that support it.

Working time

Working time is around seven minutes at 22°C; full strength is achieved after 72 hours.

Coverage per cartridge

Each dual cartridge contains 13.5 fl. oz. (400 ml) of I-Rod Adhesive, which when applied at appropriate yields the coverage figures per substrate on the table below

I-Rod size		3/4"	1"	1 1/2"		
Substrate	Linear feet per cartridge			Bond thickness	Sq. in. per cartridge	
Concrete	21'	16'	10'	0.125"	195 sq. in.	
Steel*	64'	50'	32'	0.04"	610 sq. in.	

*Painted, galvanized, or bare finish

More info at www.i-rod.com



FORMING A BOND

I-Rod Adhesive will permanently hold I-Rod in place when bolting is not an option.



13.5 OZ CARTRIDGES

Each tube contains enough adhesive to install eight feet of 1" I-Rod.



STICKY BUSINESS

I-Rod offers a heavy-duty applicator gun for using I-Rod Adhesive.